



# Fibreglass Wall Cowls

## Application

Fibreglass weather cowls are used to prevent rain and vermin from entering the building through ventilation openings.

## Construction

The aesthetically pleasing cowls are constructed using glass reinforced plastic (GRP).

This multi-layup GRP is UV & impact resistant, and can be supplied in a limited range of colours (dependent on quantity). The standard colour is gray.

Galvanised welded mesh wire is laminated into the moulding as a safety guard and to prevent vermin from entering.

| Model   | Shipping Mass (kg) | Shipping Dimensions L x W x H (mm) |
|---------|--------------------|------------------------------------|
| WCL 300 | 1,8                | 40 x 40 x 32                       |
| WCL 400 | 2,8                | 52 x 52 x 43                       |
| WCL 500 | 4                  | 63 x 63 x 53                       |
| WCL 560 | 4,4                | 69 x 69 x 59                       |
| WCL 630 | 7                  | 80 x 80 x 70                       |
| WCL 710 | 7,6                | 86 x 86 x 75                       |

| Model   | Dimensions (mm) |     |     |
|---------|-----------------|-----|-----|
|         | A               | B   | C   |
| WCL 300 | 400             | 310 | 320 |
| WCL 400 | 520             | 415 | 430 |
| WCL 500 | 615             | 525 | 530 |
| WCL 560 | 690             | 575 | 589 |
| WCL 630 | 800             | 695 | 700 |
| WCL 710 | 860             | 750 | 750 |

